

IP67



08

Part Section Showing Internal Components



★ Each side can be male or female contact

Material and spec

Coupling	Bayonet	
Shell material	PC, Nylon66, fire resistance: V-0	
Insert material	PPS, max temperature 260 °C Data: PBT, PVC	
Contact material	Brass with gold plating	
Termination	Solder: SY11, SY13, SY17, SY21, SY25, SY29 Crimp: SY17, SY21, SY25, SY29 Screw: SY21, SY25, SY29 (Ø2.5, Ø3, Ø3.5mm contact)	
Cable outer diameter range	SY11: I:3-4mm, II: 4-6.5mm SY17: 6-10mm SY25: I:10-14mm, II: 7-12mm	SY13: I: 4-6.5mm , II: 5-8mm SY21: I: 4.5-7mm, II:7-12mm, III: 5-9mm SY29:I:9-13mm, II:13-16mm
IP rating	IP67 (mated)	
Mating cycle	500	
Working temperature range	-40℃ ~ +85℃ ; Data: -20℃ ~ +70℃	
Insulation resistance	2000 MΩ	
Transmission Speed	Cat 5: 100Mbps, Cat 6: 100-1000Mbps	

SY29 Series

**SY
29**



Cable connector
Mate with SY2911, SY2911C,
SY2912, SY2913

SY2910 / P _ _ _ SY2910 / S _ _ _

Male contact


Female contact

Number of contact

1: solder, 2: screw, 3: crimp, 8: angled screw

I: 9-13mm II: 13-16mm

Cable outer diameter range





I: 9-13mm
II: 13-16mm
Cable outer diameter range



In-line cable connector C
Mate with SY2910

SY2911C/P _ _ _ SY2911C/S _ _ _



I: 9-13mm
II: 13-16mm
Cable outer diameter range






Rear-nut mount
Mate with SY2910

SY2912 / P _ _ SY2912 / S _ _




1: solder, 2: screw, 3: crimp, 8: angled screw

Number of contact



2-hole flange
Mate with SY2910

SY2913 / P _ _ SY2913 / S _ _



Solder contact spec

★Crimp contact spec see P22

★Screw contact spec see P23

Number of contact	2	3	4	7	8	8B	9	10	10B	12	16	17	20	24	26	35
Male contact face view																
Rated current (A)	50	50	25	25	25	60, 5	25, 5	25	10	10	10	10	5	5	5	5
Contact diameter(mm)	Ø3.5X2	Ø3.5X3	Ø2.5X4	Ø2.5X7	Ø2.5X8	Ø5X2 Ø1X6	Ø2.5X4 Ø1X5	Ø2.5X10	Ø1.5X10	Ø1.5X12	Ø1.5X16	Ø1.5X17	Ø1X20	Ø1X24	Ø1X26	Ø1X35
Rated voltage (AC.V)	500	500	500	500	500	500 400	500	500	500	500	500	500	400	400	400	400
Test voltage(AC.V) 1 min	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1200	1200	1200	1200
Contact resistance(mΩ)	0.5	0.5	1	1	1	0.5, 5	1, 5	1	2.5	2.5	2.5	2.5	5	5	5	5
Termination	solder / screw	solder / screw	solder / screw	solder / screw	solder / screw	solder	solder	solder / screw	solder	solder	solder	solder	solder	solder	solder	solder
Wire size (mm ² /AWG)	≤10/7	≤10/7	≤4/12	≤4/12	≤4/12	≤16/5 ≤0.75/18	≤4/12 ≤0.75/18	≤4/12	≤1.5/16	≤1.5/16	≤1.5/16	≤1.5/16	≤0.75/18	≤0.75/18	≤0.75/18	≤0.75/18
Wire size for screw termination	Min:0.5/20 Max:6/10	Min:0.5/20 Max:6/10	Min:0.5/20 Max:1.5/15	Min:0.5/20 Max:1.5/15	Min:0.5/20 Max:1.5/15	/	/	Min:0.5/20 Max:1.5/15	/	/	/	/	/	/	/	/