

M23X



IP67

IP RATING

Threaded coupling

M23Q



IP67


IP RATING

Bayonet coupling


M23X/Q Series
Material and spec

Parameter	M23X		M23Q	
Shell material	Zinc alloy with nickel plating			
Contact material	Brass with gold plating			
Insert material	power	signal	power	signal
	PA66	PBT	PA66	PBT
Insulation resistance	power	signal	power	signal
	$>10^{13}\text{m}\Omega$	9、12 pins: $>10^{10}\text{m}\Omega$ 17、19 pins: $>10^8\text{m}\Omega$	$>10^{13}\text{m}\Omega$	9、12 pins: $>10^{10}\text{m}\Omega$ 17、19 pins: $>10^8\text{m}\Omega$
Termination	Crimp			
Temperature range	$-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$			
Mating cycle	1000			
Cable outer diameter range	I: 4.5-8mm, II: 8-13mm, III: 12-15mm			
IP rating	IP67 (mated)			
Coupling	Threaded coupling		Bayonet coupling	


● M23X/Q POWER Part number system



● M23X/Q SIGNAL Part number system




● M23X Series Mating diagram



★ IP rating marked is for after mated

● **M23Q Series Mating diagram**




★ IP rating marked is for after mated




M23XDJ_TK_-3

Male contact
Threaded coupling




M23XDK_TK_-3

Female contact cable connector
Threaded coupling




M23XDJ_Z-3

Male contact
square flange receptacle
Threaded coupling



M23XDK_Z-3

Female contact
square flange receptacle
Threaded coupling




M23X Power




Male contact
angled cable connector
Threaded coupling

M23XDJ_TL_-3




Female contact
angled cable connector
Threaded coupling

M23XDK_TL_-3




Male contact angled
square flange receptacle
Threaded coupling

M23XDJ_ZL_-3



Female contact angled
square flange receptacle
Threaded coupling

M23XDK_ZL_-3




M23Q Power




Male contact
Bayonet coupling

M23QDJ_TK_-3




Female contact cable connector
Bayonet coupling

M23QDK_TK_-3




Male contact
square flange receptacle
Bayonet coupling

M23QDJ_Z_-3



Female contact
square flange receptacle
Bayonet coupling

M23QDK_Z_-3




M23Q Power



Male contact
angled cable connector

Bayonet coupling


M23QDJ_TL_-3



Female contact
angled cable connector

Bayonet coupling


M23QDK_TL_-3



Male contact angled
square flange receptacle

Bayonet coupling


M23QDJ_ZL_-3



Female contact angled
square flange receptacle

Bayonet coupling

M23QDK_ZL_-3



M23X/Q for power contact arrangement and spec

Male contact face view	Number of contact	Contact diameter (mm)	Rated voltage (AC.V)	Rated current (A)	Test voltage (AC.V)1 min
	6(5+PE)	Ø2	600	28	4000
	8(3+4+PE)	Ø1×4 Ø2×4	300 600	8 28	2500


M23X/Q for power contact spec

8A Crimp contact

※ Contact resistance: 5mΩ

※ Contact diameter: Ø1

※ Material: Brass with gold plating



8A Male crimp contact

Wire size	Stripping length	Male crimp contact p/n	Crimping tool p/n
0.14-0.37mm ² AWG 26-22	4.5mm	YJ1-20-0.5AU	CTW-0.14/4
0.5-1.0mm ² AWG 20-18	4.5mm	YJ1-20-1.0AU	CTW-0.14/4

8A Female crimp contact


Wire size	Stripping length	Female crimp contact p/n	Crimping tool p/n
0.14-0.37mm ² AWG 26-22	4.5mm	YK1-14-0.5AU	CTW-0.14/4
0.5-1.0mm ² AWG 20-18	4.5mm	YK1-14-1.0AU	CTW-0.14/4

28A Crimp

※ Contact resistance: 2.5mΩ

※ Contact diameter: Ø2

※ Material: Brass with gold plating



28A Male crimp contact

Wire size	Stripping length	Male crimp contact p/n	Crimping tool p/n
0.14-0.37mm ² AWG 26-22	7.5mm	YJ2-25.5-0.5AU	CTW-0.14/4
1-2.5mm ² AWG 18-13	7.5mm	YJ2-25.5-2.5AU	CTW-0.14/4
2.5-4mm ² AWG 13-12	7.5mm	YJ2-25.5-4.0AU	CTW-0.14/4

28A Female crimp contact

Wire size	Stripping length	Female crimp contact p/n	Crimping tool p/n
0.14-0.37mm ² AWG 26-22	7.5mm	YK2-25-0.5AU	CTW-0.14/4
1-2.5mm ² AWG 18-13	7.5mm	YK2-25-2.5AU	CTW-0.14/4
2.5-4mm ² AWG 13-12	7.5mm	YK2-25-4.0AU	CTW-0.14/4

Crimping tool

For crimping the male / female contacts




Part number	Crimping wire range
CTW-0.14/4	0.14-4mm ² AWG 25-11

M23X Signal



Male contact cable connector

Threaded coupling




M23XSJ_TK-3



Female contact cable connector

Threaded coupling




M23XSK_TK-3



Male contact square flange receptacle

Threaded coupling




M23XSJ_Z-3



Female contact square flange receptacle

Threaded coupling




M23XSK_Z-3

M23X Signal



Male contact angled cable connector

Threaded coupling




M23XSJ_TL-3



Female contact angled cable connector

Threaded coupling




M23XSK_TL-3



Male contact angled square flange receptacle

Threaded coupling




M23XSJ_ZL-3



Female contact angled square flange receptacle

Threaded coupling



M23XSK_ZL-3


M23Q Signal



Male contact cable connector

Bayonet coupling


M23QSJ_TK_-3



Female contact cable connector

Bayonet coupling


M23QSK_TK_-3



Male contact square flange receptacle

Bayonet coupling


M23QSJ_Z-3



Female contact square flange receptacle

Bayonet coupling

M23QSK_Z-3




M23Q Signal



Male contact angled cable connector

Bayonet coupling


M23QSJ_TL_-3



Female contact angled cable connector

Bayonet coupling


M23QSK_TL_-3



Male contact angled square flange receptacle

Bayonet coupling

M23QSJ_ZL-3



Female contact angled square flange receptacle

Bayonet coupling

M23QSK_ZL-3

